



ASX ANNOUNCEMENT

5 February 2025

Amended Announcement - 'Investor Presentation and Activity Update – Exploring for Large Copper Deposits'

Belararox Ltd (ASX:BRX) (Belararox or the Company), to refers to the investor presentation lodged with the ASX on 3 February 2025.

The Company has provided further information on slide 10, 16 and 18 regarding metal equivalent values and visual estimates to allow investors to better understand the presentation.

This announcement has been authorised for release by the Board of Belararox.

SHAREHOLDER ENQUIRIES

Arvind Misra

Managing Director
Belararox Limited
arvind.misra@belararox.com.au

MEDIA ENQUIRIES

Paul Berson

Corporate Storytime

paul@corporatestorytime.com

GENERAL ENQUIRIES

Belararox Limited

www.belararox.com.au

info@belararox.com.au

ABOUT BELARAROX LIMITED (ASX: BRX)

Belararox is a mineral explorer focused on securing and developing resources to meet the surge in demand from the technology, battery, and renewable energy markets. BRX's projects currently include the potential for zinc, copper, gold, silver, nickel, and lead resources.

The Company's portfolio includes the TMT Project in Argentina, targeting copper, gold, and other metals, a recent acquisition in Botswana's Kalahari Copper Belt, the Belara Project in New South Wales, focused on zinc and copper, and the Bullabulling Project in Western Australia, targeting gold.

PROJECTS

Situated within Argentina's San Juan Province, the Toro, Malambo, and Tambo (TMT) project occupies an unexplored area between the prolifically-mineralized El Indo and Maricunga Metallogenic Belts.

Belararox has already successfully identified numerous promising targets within the TMT project. These targets are set to undergo thorough exploration as part of an extensive program led by an experienced Belararox team that is currently present on-site in Argentina.





Disclaimer



Belararox Limited ("The Company") does not purport to give financial or investment advice. No account has been taken of the objectives, financial situation or needs of any recipient of this document. Recipients of this document should carefully consider whether the securities to be issued by the Company are an appropriate investment for them in light of their personal circumstances, including their financial and taxation position. The opinions and recommendations in this presentation are not intended to represent recommendations of particular investments to particular persons. This presentation does not constitute financial product advice.

To the fullest extent permitted by law, the Company and its associates or any of its directors, agents, officers or employees do not make any representations or warranties, express or implied, as to the accuracy or completeness of any information, statements, opinions, estimates, forecasts or other representations contained in this presentation. No responsibility or liability for any errors or omissions from this presentation arising out of negligence or otherwise is accepted.

This document has been prepared as a summary only and does not contain all information about the Company's assets and liabilities, financial position and prospects and the rights and liabilities attaching to the Company's securities. This document should be read in conjunction with any other reports and information provided or released by the Company.

Any securities issued by the Company are considered speculative and, there is no guarantee that they will make a return on the capital invested, that dividends will be paid on the Shares or that there will be an increase in the value of the Shares in the future. All securities transactions involve risks, which include (among others) the risk of adverse or unanticipated market, financial or political developments.

Some of the statements contained in this presentation may be forward-looking statements. Forward-looking statements include but are not limited to, statements concerning estimates of expected costs, statements relating to the advancement of the Company's investments and other statements which are not historical facts. Although the Company believes that its expectations reflected in the forward-looking statements are reasonable, such statements involve risk, and uncertainties and no assurance can be given that actual results will be consistent with these forward-looking statements. Various factors could cause actual results to differ from these forward-looking statements including the potential that the Company's projects may experience technical, geological, metallurgical and mechanical problems, changes in product prices and other risks not anticipated by the Company or disclosed in the Company's published material.

The Company confirms that it is not aware of any new information or data that materially affects the information included in the relevant market announcement and, in the case of mineral resource estimate, that all material assumptions and technical parameters underpinning the estimates in the relevant market announcement continue to apply and have not materially changed.

This presentation and contents have been made available in confidence and may not be reproduced or disclosed to third parties or made public in any way without the express written permission of the Company.



Corporate Overview

BOARD OF DIRECTORS



Mr. Neil Warburton
Non-Executive Chairman



Mr. Arvind Misra
Managing Director



Mr. Jason Ward Non-Executive Director & Exploration Director



Mr. John Traicos
Non-Executive Director

MANAGEMENT



Mr. Ben Donovan Company Secretary



Mr. Graeme Morissey
Chief Financial Officer



Mr. Jason Keys
General Manager Exploration



Dr. Steve GarwinChief Technical Advisor



Dr. Jacques Batumike
Principal Geoscientist



Mr. Arturo Guardiola Exploration Manager Argentina



Mrs. Yanina Ejarque
Project Manager
Toro Malambo Tambo

Experienced team with a successful track record of discovering world-class porphyry systems

CAPITAL STRUCTURE

Share Price*	A\$0.18
52 Week Range	\$0.125 – 0.37
Shares on Issue	143,964,113
Options expiring 13 July 2026 (66c exercise price ASX:BRXOA)	38,716,761
Performance Rights on issue	21,750,000
Cash as of 31 December 2024	\$10.475M
Debt	NIL
Market Capitalisation*	\$25.9 million
* 28 January 2025	

TMT drilling program and KCB exploration program are fully funded

SHARE REGISTER

	Shares	%
Top 20 holders	69,767,347	48.46%
Total Remaining Holders	74,196,766	51.54%



Investment Highlights - TMT

EXPLORING FOR ELEPHANTS IN A LAND OF COPPER GIANTS

TMT Project (100% BRX)

- Developing the Company's TMT
 Project in San Juan, Argentina
- A region that hosts significant copper resources owned and operated by global players

Proven Track Record

 Proven exploration team with a successful track record in the discovery and development of world-class porphyry deposits

Poised to Deliver Significant Growth

- Drilling of multiple large porphyry targets commenced in January 2025
- Recent exploration success in the region has attracted strong M&A activity






Peer Performance – Significant Value Creation Upon Discovery

Recent local discoveries in the northern San Juan region have resulted in significant value creation

- The below chart reflects the uplift in market capitalisation of select companies that have made an epithermal and/or porphyry discovery in the northern San Juan province, who are currently operating or advancing towards development
- BRX's TMT Project neighbours these major discoveries



Source 1: https://stockanalysis.com/quote/tsx/FIL/market-cap/; https://stockanalysis.com/quote/tsx/ngex/market-cap/

Source 2: Filo Mining Corp - TSX Release dated 13 May 2021 Source 3: NGEx Minerals – TSX Release dated 4 April 2023

Source4: BHP Group Limited - ASX Release dated 30 July 2024 https://announcements.asx.com.au/asxpdf/20240730/pdf/0662g2pf3gz722.pdf Source 5: NGEx Minerals – TSX Release dated 12 August 2024



TMT Project (100% BRX) – San Juan, Argentina


EXPLORING FOR ELEPHANTS IN A LAND OF COPPER GIANTS

Highly prospective 32,000 hectares landholding located in an area boasting large copper porphyry deposits

Strategically located near major copper and gold discoveries such as Filo del Sol (Lundin), Los Helados (NGEx Minerals), Josemaría (Lundin), and El Encierro (Barrick Gold and Antofagasta)

Recent exploration success in the region has attracted significant interest from major mining companies and strong M&A activity (BHP and Lundin joint C\$4.1 billion bid for Filo Corp in July 2024)

Recent assay results and 3D geochemical modelling have defined the presence of multiple significant copper/gold porphyry targets – BRX to drill high priority targets.





Two High Priority Targets to be Drilled Tested

Systematic Exploration

- Target-rich environment
- 16 priority targets identified by BRX to date

Earthworks


- Brig SRL to receive 50% of all fees in BRX shares
- Road access and access to tracks for drilling program complete.

Camp

Operating with a capacity of 60 staff

Drilling – 2 Rigs at Site

- Conosur to take 5% of its fee in BRX shares.
- Tambo South drilling commenced 19 January 2025
- Malambo drilling to commence 7 February 2025



TMT project concession areas showing hyperspectral anomalies identified by Garwin (2023). The concessions in dark green are those related to drilling tasks, while those in light green are prospective.



Tambo South Fieldwork - Drilling Commenced 19 January 2025












Tambo South – Planned Drillholes

2024/25 Drilling Program

- 2,600 m of diamond drilling planned in two drill holes.
- Targets high probability porphyry system (interpreted from 3D geochemical modelling) within 900m from surface.
- Holes will also intersect shallower target interpreted.
- Planned holes located below quartz veins and surface molybdenum anomaly.
- Drill holes planned to a depth of 1200 to 1400m.

3D section view of the Tambo South target looking N showing planned drillhole locations plotted with geology surface mapping and the Cohen and Halley 3D geochemical models.





Drilling Update TMT-TSU-DDH-001

Hole summary

• Target depth: 900 m


• Planned depth: 1300


• Current depth: 524 m

(4-Feb-2025)

Highlight

- Covellite was observed in the core between 286.9 m and 288 m (0.2% visual estimate) as elongate crystals in fractures and veinlets.
- The presence of covellite is encouraging as:
 - it is an indicator of indication of high sulphidation overprint
 - suggests the potential for high-grade copper mineralization at depth








Visual estimates of mineral abundance should never be considered a proxy or substitute for laboratory analyses where concentrations or grades are the factor of principal economic interest. Visual estimates also potentially provide no information regarding impurities or deleterious physical properties relevant to valuations. Assay results are expected by the end of April.



Malambo – Drill Road Construction, Magnetics Survey and Fieldwork










Malambo – Collar Locations With Hydrothermal Alteration






Malambo – Planned Drillholes


2024/25 Drilling Program

- Drilling to commence 7 February 2025
- 3400m of diamond core drilling planned
- 3 drillholes target below outcropping potassic alteration zone
- Planned hole depths of 1000m to 1200m
- Targets high probability porphyry system within 600m from surface (interpreted from 3D geochemical modelling)
- Shallower targets will also be tested
- Final location of the 3rd hole informed by the drilling of DDH1 and DDH2

Oblique-view (Looking downwards 15° towards the north), showing the Malambo MVI geophysics survey completed in December 2024 with the planned Malambo drillholes and molybdenum (Mo) in surface samples and Malambo porphyry targets predicted by the porphyry metal zoning models of Halley et al. (2015) and Cohen (2011).

(ASX 28-01-2025)







TMT Project – Lola 2 Target





TMT Project – Lola 2 Target

Geology

- Fine-grained diorite, mod. to strong phyllic alteration + high fracture abundance.
- Two vein-like structures were observed cross-cutting the diorite.

A) TMTA-0154:

 Quartz-Carbonate with copper carbonates with Azurite (1%) + Malachite (0.3%).

Assays results:

Cu 10,500 ppm; Mo 2.15 ppm; Ag 133 g/t


B) TMTA-00160:

Massive Quartz with Pyrite (1%).

Assays results:

Cu 738 ppm; Mo 3.71 ppm; Ag 29.9 g/t





Visual estimates of mineral abundance should never be considered a proxy or substitute for laboratory analyses where metal concentrations or grades are the factor of principal economic interest. Visual estimates also potentially provide no information regarding potential impurities or deleterious physical properties relevant to valuations.







TMT Project - Emilia Vein







Description

Interpreted as a low-medium sulphidation epithermal system distal to a porphyry system.


- Quartz Vein (90%)
- Outcrop length of 300 meters
- Average thickness of 1-2 meters
- Vein and vein breccia in a diorite host rock
- Pseudo vuggy textures filled with goethite
- Fluid textures present
- Py 0.1-0.3%

Assays expected by end of March 2025.

Visual estimates of mineral abundance should never be considered a proxy or substitute for laboratory analyses where metal concentrations or grades are the factor of principal economic interest. Visual estimates also potentially provide no information regarding potential impurities or deleterious physical properties relevant to valuations.



Satellite-Supported Spectral Zone of Interest



Panoramic-view, looking west towards the Chile – Argentina border from the Malambo drill access road (approx. 12km field of view). The dashed line approximately outlines the northerly-trending, regional zone of spectral interest that extends > 30km through the western part of the TMT project area, through Tambo VI and Tambo VI-2, Tambo South and Tambo 5, to Tambo North and Tambo North 2.




TMT Project – Key Activities

Maiden Drilling commenced at TMT Project 19-January 2025


Completed Works

- ✓ Target generation
- Reconnaissance mapping
- **✓** Drill target definition
- Drilling contract executed
- Re-open access to main camp











Investment Highlights - KCB



KCB Project (100% BRX)

 Kalahari Copper Belt project in Botswana - A region hosting significant copper-silver resources owned and operated by global players

Proven Track Record


 Proven exploration team with a successful track record in the discovery of copper deposits in the Central African Copper Belt

Poised to Deliver Significant Growth

 Kalahari Copper Belt has the highest potential for undiscovered copper in sediment-hosted stratabound copper deposits – USGS, 2010



MOD Resources ... a Demonstrable Botswana Copper Success Story



Shares in ASX-listed MOD Resources **increased as much as +1,600**% following its copper discovery in the Kalahari copper belt in Botswana, before eventually being acquired by Sandfire for A\$167m in 2019




Asset

- Project located in the Kalahari Copper
 Belt in Botswana
- 14 tenements covering 4,268 km² of land in prospective areas

Highlights

- The observed structures in areas with known mineralisation extend to BRX tenements
- Most tenements along the interpreted N'gwako Pan Formation and D'Kar Formation contact (NPF-DKF)
- Known resources concentrated along the "central corridor" aligned NE-SW
- Recent discoveries indicate mineralisation outside of this corridor





Field Program Underway

Positive Initial Assessment

- Promising targets identified in Dr. Jacques Batumike's review
- Focus on D'Kar/Ngwako Pan contact and strike extensions of existing deposits.
- Tenements with potential for target contacts inferred from existing data.

Staged Exploration Strategy

 Inspired by successful exploration activities of Sandfire Resources, Cobre Limited, and MMG Limited at Khoemacau.

2025 Exploration Program Objectives

- Positive community engagement
- Verify regolith mapping interpreted from Aster and Sentinel-2 data
- Soil sampling program in 8 tenements
- AMT survey in 5 tenements for potential shallow targets
- EM survey on three highly ranked targets
- Drill testing after target definition by June-July 2025

Community meeting at Matsaudi January 2025







KCB Project – Key Activities

Indicative Timing for KCB Activities














Investment Highlights - Australia

Belara Project

- Comprehensive tenement package spanning the northern extent of the Hill End Trough.
- Drilling intersected several shallow, high-grade zones including:
 - 7m @2.54% Cu, 2.22 % Zn (from 78m)
 - 5m @1.19% Cu, 6.8% Zn (from 51m)
- Mineral resource estimate for Belara and Native Bee with Inferred Resources of 5Mt @ 3.41 % ZnEq with mineralization open down dip and along strike.

Bullabulling Project

- Parallel to the >3MOz Bullabulling goldfield and within a structurally analogous setting.
- Several new potential Lithium-Caesium-Tantalum ("LCT") pegmatite targets were identified, soil anomalies up to 324ppm Li
- Two (2) of the largest coherent lithium soil anomalies (>80ppm Li)
 can each be traced over 500m within a highly prospective > 3km long
 structural corridor with anomalous Li values





Belararox Limited (ASX:BRX)

Arvind Misra

Managing Director arvind.misra@belararox.com.au

Paul Berson

Corporate Storytime
paul@corporatestorytime.com

www.belararox.com.au

This presentation has been authorised for release by the Board of Directors.





Competent Person Statements

Competent Person Statement

Mr Jason Ward is a Competent Person who is a Fellow and Chartered Professional of the Australasian Institute of Mining and Metallurgy. He is also a director of Condor Prospecting and Belararox Limited. Mr Ward has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 Edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Mr Ward consents to the inclusion in the report of the matters based on his information in the form and context in which it appears.

The information in this announcement that relates to exploration results in the TMT Project is extracted from ASX announcements listed below and compiled by Mr Jason Ward.

- TMT Update Drilling programme ready at Malambo target 2 December 2024
- Malambo 3D Geochemical Interpretation Confirm Copper Targets 28 May 2024
- Assay Results from Malambo Confirm Porphyry Style Target 16 May 2024
- Assay Results from Toro Tenement Support Epithermal Targets 29 April 2024
- TMT Project (Tambo South): Geological Mapping Confirms Prospectivity for a High Sulphidation / Porphyry System 18
 Mar 2024
- TMT Project Malambo Target: Geological Mapping Supports the Presence of a Porphyry System and Provides a Focus for Exploration 29 Feb 2024
- TMT Operational Update: Geological Mapping Supports the Porphyry Potential at Toro 22 Jan 2024
- Amended TMT Fieldwork Update 12 Dec 2023
- TMT EIA Approval 1 Sept 2023
- TMT Project 2012 JORC Report verifies Zinc Mineralisation 17 Jul 2023
- TMT Project Environmental Impact Assessments Lodged 8 Jun 2023
- Amended Announcement Porphyry Prospectivity Confirmed with additional TMT targets Identified 23 May 2023
- Porphyry Prospectivity Confirmed with Additional TMT Targets Identified announced 18 May 2023
- TMT project acquired announced 23 March 2023

Cautionary Statement: The intercepts from the 1996-1997 Sonoma Resource Development Argentina S.A. Diamond Drilling ("DD") and Reverse Circulation ("RC") drilling campaign are suitable for the reporting of 'Exploration Results' for mineral prospectivity, further exploration work would be needed to produce a 'Mineral Resource'.

The information in this announcement that relates to Belara and Bullabulling exploration results is extracted from ASX announcements listed below and compiled by Mr Jason Ward.

- Belara Gold Exploration Update High Grade Rock Chip Results 2 April 2024
- Infill Surface Sampling at Bullabulling Returns 646ppm Li²O announced 6 February 2024
- Bullabulling Lithium and Gold Anomalies announced 25 October 2023
- Belara Exploration Update 25 September 2023
- Belara Regional Exploration Update 29 Aug 2023
- Bullabulling Assay Results Confirm LCT Pegmatites 26 June 2023
- Amended Update Bullabulling Project 8 June 2023
- Native Bee Drilling Results 12-May-2023
- Bullabulling Exploration Update 5-Apr-2023
- Significant Belara and Native Bee Maiden Resource Estimate 03 November 2022
- Met tests show saleable concentrates & excellent recoveries 17 October 2022
- EM Surveys Confirm Extension of Mineralisation at Native Bee 06 October 2022
- High Grade Massive Sulphide Confirmed 12 July 2022
- New Assay Results at Belara 26 July 2022
- 34 New Targets Expand Belara Exploration Area 10x 31 May 2022
- Data Review and Exploration Update 24 February 2022
- IPO prospectus 1 November 2021

The information in this announcement that relates to KCB Project is extracted from ASX announcements listed below and compiled by Mr Jason Ward.

• Binding Agreement Executed to Acquire Kalahari Copper Project in Botswana - 12 September 2024

ASX Announcements Availability

The announcements are available to view at www.belararox.com.au and www.asx.com.au. The Company confirms that it is unaware of any new information or data that materially affects the information included in the original market announcements. The Company confirms that the form and context in which the Competent Person's findings are presented have not been materially modified from the original market announcements.



APPENDIX C: JORC (2012) CODE TABLE 1

The following JORC (2012) Code Table 1 has been prepared for the Tambo South target

Criteria	JORC Code explanation	Commentary
Sampling techniques Drilling techniques	 Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling. Include reference to measures taken to ensure sample representativity andthe appropriate calibration of any measurement tools or systems used. Aspects of the determination of mineralisation that are Material to the Public Report. In cases where 'industry standard' work has been done; this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases, more explanation may be required, such as where there is coarse gold with inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant the disclosure of detailed information. Drill type (e.g. core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard) 	 Determination of mineralisation of hand specimens referenced in this presentation are quantitative, based on visual field estimates made by the geologists. Diamond drilling was undertaken to obtain core samples PQ and HQ diamond drill core. Triple-tube wire line standard equipment. Surveys use DeviShot tool. Core is oriented using spear technique.
·	tube, depth of diamond tails, face-sampling bit or other types, whether the core is oriented and if so, by what method, etc).	3-1-1-7-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-
Drill sample recovery	 Method of recording and assessing core and chip sample recoveries and results assessed. Measures are taken to maximise sample recovery and ensure the representative nature of the samples. Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material. 	 For diamond drilling recovery is recorded for every run. In general core recovery is in excess of 99%. There is insufficient core loss for this to have a bias.
Logging	 Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies. Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography. The total length and percentage of the relevant intersections logged. 	 At selected and systematic locations during the Anaconda geological mapping, descriptions of lithology, alteration, mineralisation and other features were systematically recorded in the field and encoded into an Excel sheetfor future reference. Samples are being collected in a systematic and selective fashion with descriptions of lithology, alteration, mineralisation and other features systematically recorded in the field and encoded into an Excel sheet for future reference. Visual estimates of mineral abundance based on observed outcropping minerals should never be considered a proxy or substitute for laboratory concentrations where grades are the factor of principal economic interest. Visual estimates also potentially provide no information regarding impurities or deleterious physical properties relevant to valuations. All visual estimates have been made by experienced Geologists.



BELARAROX LIMITE

Sub-sampling techniques and sample preparation	 If core, whether cut or sawn and whether quarter, half or all core taken. If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry. For all sample types, the nature, quality and appropriateness of the sample preparation technique. Quality control procedures adopted for all sub-sampling stages to maximise the representativity of samples. Measures are taken to ensure that the sampling is representative of the in-situmaterial collected, including, for instance, results for field duplicate/second-half sampling. Whether sample sizes are appropriate to the grain size of the sampled material. 	 At the rig, core is photographed, initial geotechnical logging is performed, and the core is oriented. Core is photographed, logged, cut and sampled by project personnel at a core logging area at the camp. Geological and geotechnical logging is at a level of detail to support future Mineral Resource Estimation and other mining and metallurgical studies. Core is sampled continuously down the hole Sample lengths are generally 4 metre lengths Lengths where visual estimates of mineralization 20m at > 0.3% chalcopyrite (> 0.1% Cu) trigger collection of samples every 2m 2m samples use half core 4m samples use quarter core In both half core and quarter core cutting/sampling, the 0° orientation line is used to cut the core to avoid sample bias.
Quality of assay data and laboratory tests	 The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total. For geophysical tools, spectrometers, handheld XRF instruments, etc., the parameters used in determining the analysis include instrument make and model, reading times, calibration factors applied and their derivation, etc. Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established. 	 ALS Patagonia has been selected to undertake analyses using the following: ME-MS61 (Four acid digestion followed by ICP-MS measurement) Au-AA23 (Au by fire assay and AAS) HYP-PKG (TerraSpec® 4 HR scanning and aiSIRIS™) Quality control procedures are as follows: Blanks every 50 samples Standards every 50 samples Duplicates 3 per 100 samples Acceptable levels of accuracy and precision have been established to date in the soils, talus and rock chip samples. Results not yet received for the core samples.
Verification of sampling and assaying	 The verification of significant intersections by either independent or alternative company personnel. The use of twinned holes. Documentation of primary data, data entry procedures, data verification, addata storage (physical and electronic) protocols. Discuss any adjustments to assay data. 	 Procedures for sampling and assaying are well documented. This includes the verification of significant intersections by the geological team (both the original logger and others as available.)



Location of data points

- Accuracy and quality of surveys used to locate drill holes (collar and downhole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.
- Specification of the grid system used.
- Quality and adequacy of topographic control.

- GPS locations for the Anaconda geological mapping activities are being captured by handheld GPS units in the field and later encoded into an Excel spreadsheet containing the surface samples with descriptions of lithology, alteration, mineralisation and other features.
- GPS sample locations are being captured by handheld GPS units in the field and later encoded into an Excel spreadsheet containing the surface samples with descriptions of lithology, alteration, mineralisation and other features.
- GPS co-ordinates were recorded in Eastings and Northings for WGS 1984, UTM Zone 19s or converted afterwards into WGS 1984, UTM Zone 19s
- The data discussed in the current ASX Release includes two (2) different multispectral spaceborne datasets for the location of the twelve (12) targets:
 - o [i] Advanced Spaceborne Thermal Emission and Reflection Radiometer ("ASTER"); and
 - o [ii] Sentinel-2.
- The data is initially recorded by satellites and the processing and interpretation were delivered in the coordinate system of WGS84 Zone 19S.
- The survey control is appropriate for the interpretation of the processed ASTERand Sentinel-2 to deliver regional targets as surface expressions that
 - likely to represent surface expressions of high-sulphidation epithermal and/or porphyry-style mineral systems.
- Follow-up on the ground exploration activities, comprised of surface sampling and Anaconda mapping have used hand-held GPS to assist with the physical location of the collected samples.
- The location of the rock samples described in this presentation are:

ID	easting	northing	elevation
TMTA00154	435016	6768286	3378
TMTA00160	435995	6768970	3377

Drillholes are located with handheld GPS and the alignment of the rig setup uses a handheld compass. Topographic control is via the GPS and the satellite 30m DEM.



Data spacing and distribution

- Data spacing for reporting of Exploration Results.
- Whether the data spacing, and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore Reserve estimation procedure(s) and classifications applied.
- Whether sample compositing has been applied.

- The surface sample locations that are in the process of being collected vary from clusters at outcrops to surface samples aiming to cover a board area, at a spacing ~200m apart to cover and identify high-sulphidation epithermal and/or porphyry mineral systems.
- The data discussed in the current ASX Release deals with two (2) different multispectral spaceborne datasets:
 - [i] Advanced Spaceborne Thermal Emission and Reflection Radiometer ("ASTER"); and
 - o [ii] Sentinel-2.
- The data is initially recorded by satellites and the processing and interpretation were delivered in the coordinate system of WGS84 Zone 19S.
- Multispectral image sensors simultaneously capture image data within multiple wavelength ranges (bands) across the electromagnetic spectrum.
 Each band is commonly described by the band number and the band wavelength centre position.
- The ASTER processed datasets of a resolution of 15m for Visible Near Infrared ("VNIR) or 30m for Short Wavelength Infrared ("SWIR").
- The Sentinel-2 resolution ranges from 10m to 60m dependent on bandwidth.
- The survey control and data resolution are appropriate for the interpretation of the processed ASTER and Sentinel-2 to deliver regional targets as surface expressions that are likely to represent surface expressions of high-sulfidation epithermal and/or porphyry-style mineral systems.
- Follow-up on the ground exploration activities, comprised of surface sampling and Anaconda mapping have used handheld GPS to assist with the physical location of the collected samples. Surface samples collected included Outcrop/Rock Chip, Talus, and Float Samples.

Orientation of data in relation to geological structure

- Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.
- If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.
- The surface sample locations that are in the process of being collected vary from clusters at outcrops to surface samples aiming to cover a board area, at a spacing ~200m apart to cover and identify high-sulphidation epithermal and/or porphyry mineral systems.
- The data discussed in the current ASX Release deals with two (2) different multispectral spaceborne datasets:
 - [i] Advanced Spaceborne Thermal Emission and Reflection Radiometer ("ASTER"); and
 - o [ii] Sentinel-2.
- Multispectral image sensors simultaneously capture image data within multiple wavelength ranges (bands) across the electromagnetic spectrum.
 Each band is commonly described by the band number and the band wavelength centre position.
- The interpretation of the regional geological structures, based on a number of sources and datasets (e.g. porphyry potential [Ford, et al, (2015) & USGS



		 (2008)], crustal lineaments [Chernicoff, et. al, (2002)], regional gravity, regional magnetics, regional and local geology [SegemAR (2023) & Servicio Nacional de Geologia y Minera (2023)] had been utilised to confirm if the interpretation of alteration and/or mineralisation from the processed ASTER and Sentinel-2 datasets. Geological interpretation is then based on the responses displayed in the imagery against known surface hydrothermal alteration and/or surface geology associated with key mineral deposits. Geological analogues are a useful tool for delineating similar surface expressions of mineralisation. Follow-up on the ground exploration activities, comprised of surface sampling and Anaconda mapping, using handheld GPS to assist with the physical location of the collected samples. Surface samples collected included Outcrop/Rock Chip, Talus, and Float Samples, these samples are selective for outcrop or spatially distributed across the ground surface for Talus and Float samples to generate a first-pass geochemical understanding of the exposed geology.
Sample security	The measures taken to ensure sample security.	 Samples are bagged, numbered, zip tied and transported with dispatch information by project staff directly to the office/warehouse in San Juan. Routinely (fortnightly) samples are then transported to Mendoza ALS preparation lab.
Audits or reviews	The results of any audits or reviews of sampling techniques and data.	 Sampling techniques have been developed in consultation with the Competent Person Jason Ward and Dr Steve Garwin. No audits or reviews have been undertaken to date.



SECTION 2 REPORTING OF EXPLORATION RESULTS

(Criteria listed in the preceding section also apply to this section.)

Criteria	JOR	C Code explanation	ation Commentary					
Mineral tenement and land tenure status	 Type, reference name/number, location and ownership, including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national parks and environmental settings. The security of the tenure held at the time of reporting and any known impediments to obtaining a license to operate in the area. 		the Term mineral t secures r <u>api.mark</u> 6A11306	the Terms Sheet for the Acquisition of the Fomo Ventures No1 Pty LtdArgentin mineral tenures are presented in Belararox Limited (ASX: BRX) ASXRelease "Bel secures rights to acquire Project in Argentina" dated 03-Jan-2023 https://cdn-api.markitdigital.com/apiman-gateway/ASX/asx-research/1.0/file/2924-02618641130657?access_token=83ff96335c2d45a094df02a206a39ff4				
	Tenure Name	Tenement	Te	enure Type	Area (Ha)	Grant Date	Expiry Date	
	LOLA	1124-181-M-2016	Dis	covery claim	2,367.0	29 Dec 2016	Not Applicable	
	MALAMBO	425-101-2001	Dis	covery claim	3,004.0	13 Aug 2019	Not Applicable	
	MALAMBO 2	1124-485-M-2019	Dis	covery claim	414.1	24 Jun 2021	Not Applicable	
	MALAMBO 3	1124-074-2022	Dis	covery claim	2,208.0	Application	Application	
	MALAMBO 4	1124-073-2022	Dis	covery claim	2,105.0	27 Nov 2023	Not Applicable	
	TAMBO SUR	1124-188-R-2007	Dis	covery claim	4,451.0	11 Jul 2019	Not Applicable	
	TAMBO SUR I	1124-421-2020	Discovery claim		833.0	9 Nov 2021	Not Applicable	
	TAMBO SUR II	1124-420-2020	Dis	covery claim	833.0	13 Dec 2021	Not Applicable	
-	TAMBO SUR III	1124-422-2020	Discovery claim Discovery claim Cateo Cateo		833.0	Application	Application	
-	TAMBO SUR IV	1124-299-2021			584.0	3 Dec 2021	Not Applicable	
	TAMBO SUR V	1124-577-2021			7,500.0	Application	Application Not Applicable	
	TAMBO SUR VI	1124-579-2021			5,457.0	5 Nov 2024		
	TORO	1124-528-M-2011	Dis	covery claim	1,685.0	2 Jul 2013	Not Applicable	
Note 1: For a Discovery Claim, there is no expiration date Note 2: All mineral tenures are held by GWK S.A.			d while the min	imum investment plan is fo	ollowed.			
Exploration done by other parties	Acknowledgment ar	nd appraisal of exploration by other p	parties.	covered titled 'Bit Zinc Min aforeme Results' (2012) Co The inter sources a crustal lit	in the Belararox Limite anding Agreement exectorial eralisation (266m @ 0 ntioned ASX Release or are yet to be reported ode. Transport of the region and datasets (e.g. porported neaments [Chernicoff, and local geology [Seg	to the JORC nal geological structures, bothyry potential [Ford, et al, et. al, (2002)], regional gra	ated 23 rd Mar 2023 and ct in Argentina Significant ical drilling.". Note: the ment', and the 'Exploration ased on a number of (2015) & USGS (2008)], wity, regional magnetics, acional de Geologia y Minera	
				regional (2023)] h mineralis	and local geology [Seg nad been utilised to co sation from the proces	emAR (2023) & Servicio Na	ncional de Geologia y of alteration and/or datasets.	



	Geold
ARC	
LAR.	
M	

		 for use in the Garwin (2023) study, and the processed data is included in images within this ASX Release. Fathom Geophysics processed the data reported Malambo Geophysics into MVI Amplitude, MVI Induced, MVI Remanent datasets. MVI Amplitude figures have been used in this announcement.
Geology	Deposit type, geological setting and style of mineralisation.	 Regional Geology: The TMT project is within or in proximity to a number of the significant regional metallogenic belts of South America, (1) the Andean Metallogenic Belt, (2) the El Indio Metallogenic (Cu-Au) Belt, and (3) the Maricunga Metallogenic (Cu-Au) Belt. Toro (1124-528-M-11) tenure and Specific Geology (from historical reports): The identified rocks include the Valle del Cura Formation (Eocene), composed mainly of red conglomerates, sandstones, tuffs, andesites and pyroclastic ignimbrites. Some of these rocks outcrop on the surface, with tuffaceous breccias being intersected in historical drill holes. The sequence is intruded by subvolcanic bodies pseudo concordant to stratification, "intrusivos Miocenos", the source of the hydrothermal alteration-mineralization in the area. Rhyodacitic - dacitic rocks, altered by advanced argillic and phyllic alteration dominate the area. Silicification, argillic, and propylitic alteration are present in the Toro project tenure. Stockworks and at least one (1) Breccia Pipe have beenidentified during historical exploration activities at the Toro project. The Targets' interpreted from the Satellite Imagery: 12 prospective targets are considered to represent surface expressions of high-sulphidation epithermal and/or porphryr-style mineral systems based on the interpretation of processed ASTER and Sentinel-2 datasets and comparison to regional GeologicalAnalogue deposits with comparable surface mineralisation (South to North):

Drill hole Information	,	remote sensing interpretation of the geology. • Filo del Sol deposit - Geological Analogue (Ausenco Engineering Canada Inc, 2023) (Filo Mining Corp., 2020): • The Filo del Sol deposit has an estimated Total Mineral Resource of 644Mt @ an average grade of 0.31% Cu, 0.32g/t Au, & 10.1 g/t Ag with cut-off grade varying for elements, oxide, sulphide, and AuEq, refer to source document for the cut- off grade (Ausenco Engineering Canada Inc, 2023). The Filo del Sol deposit is associated with oxide & sulphide ores that are strongly associated with siliceousalteration (mapped silica and residual quartz), surrounded by quartz-alunite alteration. • The Filo del Sol Cu-Au-Ag deposit has been used as a geological analogue since it shows a similar response to the siliceous alteration (silica and residual quartz)and similar regional structural features, with N-S major lineament crosscut by aNW-SE structure. • Valadero - Geological Analogue (Holley, 2012) • The Veladero deposit displayed clear links between the ASTER thermal image and the surface-mapped silica / residual quartz alteration. The final pit predominantly targeted the surface ASTER interpreted Jarosite & Pyrophyllite. • The Veladero surface alteration and mineralisation mapping presented againstthe final pit design by Holley (2012) includes silicification, quartz-kaolinite-sulphur, quartz-alunite, quartz-illite, chlorite-epidote, & chlorite-epidote. • Summary information for drillholes • TMT-TSU-00001 • East • North							
	metres) of the drill hole collar	•							
	Dip and azimuth of the holeDownhole length and interception depth	HoleId	Easting	Northing	Elevation	Azi	Dip	Target Depth]
	 Hole length. If the exclusion of this information is justified on the basis that 	TMT-TSU-DDH-001	428,685	6,791,500	4,200.25	90	80	1,300.00	
	the information is not Material and this exclusion does not detract from theunderstanding of the report, the Competent Person should clearly explain why this is the case.								
Data aggregation methods	 In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated. Where aggregate intercepts incorporate short lengths of high-grade results and longer lengths of low-grade results, the procedure used forsuch aggregation should be stated and some typical examples of such aggregations should be shown in detail. The assumptions used for any reporting of metal equivalent valuesshould be clearly stated. 	 No data aggreg 							
Relationship between mineralisation	 These relationships are particularly important in the reporting of Exploration Results. If the geometry of the mineralisation with respect to the drill hole 	 Interpretation and datasets (elineaments [Ch 	g. porphyry	potential [For	d, et al, (2015	5) & US	SGS (20		



widths and intercept lengths	 angle is known, its nature should be reported. If it is not known and only the down hole lengths are reported, thereshould be a clear statement to this effect (eg 'down hole length, truewidth not known'). 	 and local geology [SegemAR (2023) & Servicio Nacional de Geologia y Minera (2023)] had been utilised to confirm if the interpretation of alteration and/or mineralisation from the processed ASTER and Sentinel-2 datasets. Geological interpretation is then based on the responses displayed in the imagery against known surface hydrothermal alteration and/or surface geologyassociated with key mineral deposits. Geological analogues are a useful tool for delineating similar surface expressions of mineralisation. Follow-up on the ground exploration activities is required to confirm the remote sensing interpretation of the geology and in particular confirm thedimensions of any surface expression of alteration and/or mineralisation. Field mapping has been completed on the Toro South and Toro North Targets; the field mapping is substantially complete for the Toro Central Target. All statistical information presented in this ASX Release is inclusive of Field Duplicates and assayed samples that have been allocated ½ of the lower detection limit, for any elements reported as below the detection limit.
Diagrams	 Appropriate maps and sections (with scales) and tabulations of interceptsshould be included for any significant discovery being reported These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views. 	Appropriate maps and sections are displayed in the body of the ASX Release.
Balanced reporting	 Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/orwidths should be practised to avoid misleading reporting of Exploration Results. 	 Follow-up on the ground exploration activities is required to confirm the remote sensing interpretation of the geology and in particular confirm the dimensions of any surface expression of alteration and/or mineralisation. Field work is progressing across the targets to follow up the remotesensing work and new targets
Other substantive exploration data	Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.	 'Other substantive exploration data' is summarised in the Belararox Limited (ASX:BRX) ASX Releases dated: 23rd May 2023: Amended Announcement – Porphyry Prospectivity Confirmed with additional TMT targets identified; 17th July 2023: TMT project in Argentina Significant Zinc Mineralisation(266m @ 0.76% Zn) verified and reported under the JORC (2012) Code; 30th Oct 2023: TMT Project – Field Work Commenced and Additional High Sulphide Epithermal & Porphyry Targets Characterised; 12th Dec 2023: TMT Project – Field Work Update; and 22nd Jan 2024: TMT Project Operational Update: Geological Mapping Supports the Porphyry Potential at Toro 28thMay 2024: TMT Project: Malambo 3D Geochemical Interpretation Confirms Copper Porphyry Style Targets The information on the drone survey conducted by DAMS is as follows: Sensor:



		 Terrain Following: Utilized SRTM data for terrain following to minimize topographic effects. Groundspeed: 3-6 m/s (dependent on terrain and environmental conditions)
Further work	 The nature and scale of planned further work (eg tests for lateralextensions or, depth extensions or large-scale stepout drilling). Diagrams clearly highlighting the areas of possible extensions, includingthe main geological interpretations and future drilling areas, provided this information is not commercially sensitive. 	 Regional mapping and sampling are ongoing at TMT. Exploration is focused on the spectral targets discussed in this JORC Table 1 and the presentation as well as the new targets discovered in field activities including Lola-2, Emilia Vein and a new spectral zone of interest.